



GE
Security

Product Data Sheet

AS610DUM

Dummy outdoor siren with single blue beacon

Standard Features

- Attractively shaped housings
- High-quality dual skinned design
- 120 dB @ 1 m sound output
- 300 x 210 x 87 mm
- Lead acid battery back-up for up to 7.2 Ah
- Steel inner cover with foam resistant grid
- Fully potted electronics
- Pry-off and opening tamper detection
- Strobe flash light
- Self detection of cable cutting or tampering
- Installer friendly
- Automatic polarity selection
- Independent hold-off for both beacon and siren
- Choice of cut-off time

AS610DUM

Dummy outdoor siren with single blue beacon

Specifications

Power supply	13.0 to 14.2 VDC
Standby current	25 mA
Current consumption	600 mA
Voltage step-up converter	N/A
Tamper monitoring relay	N/A
Sound output at 1 m	N/A
Frequency	1.8 to 2.8 kHz
Cut-off timer	Preset at 3 min. Adjustable 5 min., 10 min., 20 min.
Operating temperature	-25 to +55°C
Self-activating (with battery)	N/A
Recommended battery	1.2/7.2 Ah
Material	Polycarbonate/Inox
Weight	3 kg
Dimensions	300 x 210 x 87 mm
Beacon	
Supply voltage	13.0 to 14.2 VDC
Operating current	110 mA
Light output	100,000 peak lumens
Flash frequency	60 flashes/minute
Spike suppression network	Standard fitted

Ordering Information

Part No.	Description
AS610DUM	Dummy outdoor siren with single blue beacon

