



ATS1475

Hitag II Proximity Smart Card voor CS1700 en ATS1190/ATS1192 lezer.

Product overview

These cards are to be used on ATS readers. The cards are unprogrammed and have the number printed for easier administration. Both the smart chip and antenna are embedded inside the card. Printing is possible on the card using any industry standard printer and because each card has superior finished surface you will always have excellent printing results.



Details

- Read/Write capability
- Ability to program a unique 4-billion, 4-byte security code
- Packed by 10

ATS1475

Hitag II Proximity Smart Card voor CS1700 en ATS1190/ATS1192 lezer.

Technische specificaties

System

Reading distance	0 to 60 cm
Custom data model	No
Supported readers	ATS Proximity Readers

Technology

Credential type	Proximity
Credential operating frequency	125 KHz
Supported technology	HiTag 2 125 kHz

Printing

Direct surface printing	Yes
-------------------------	-----

Ordering information

Minimum order quantity	1
Cards/tags in package	10

Physical

Material	PVC
Form factor	CR80 (Credit)
Physical dimensions	86 x 54 mm
Colour	White



Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar nl.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 August 2022 - 10:29