

ATS Voice Reporting Module

ATS7200

Voice reporting

The Advisor MASTER is capable of playing back recorded voice messages using the optional ATS7200 module. Two modules can be connected per control panel, each having a recording time of 35 seconds divided into 8 messages. Voice messages are programmed to report on the occurrence of specific reporting codes. Some reporting codes are general alarms (Burglar Alarm, Fire Alarm, Tamper Alarm ...), while others are zone specific, that is, you can link a reporting code to specific zones. This means any zone activation or event happening (including technical alarms) can trigger a voice message.

Specifications

Power supply	12 VDC via ribbon cable from control panel
Supply current	50 mA
Recording capacity	8 messages (total recording time ~ 35 sec.)
Dimensions	80 x 50 x 20 mm
Weight	123 g
Temperature	10° to +50°C
Non-volatile memory	Yes, temporary (min. 5 hours)
Automatic gain control during recording	Yes
Acknowledge by DTMF code	



Ordering Information

ATS1801	ATS Computer and printer interface
ATS1806	ATS Universal Interface for an Ethernet based IP connection
ATS7100	ATS ISDN - B channel communicator
ATS7110	ATS ISDN - B & D channels communicator
ATS7200	ATS Voice Reporting Module
ATS7300	ATS GSM Module for Reporting and U/D