



GE
Security

Product Data Sheet

BS127N

Sealed Lead-Acid Battery - 12V 7.2Ah



Standard Features

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS127N

Sealed Lead-Acid Battery - 12V 7.2Ah

Specifications

Power supply	12 VDC
Nominal capacity	7.2 Ah, 20 h rate
Max. charge voltage at +20°C	13.8 VDC
Max. charge current	2.16 A
Max. discharge current	35 A
Internal approx. resistance	21 mohm
Temperature	
Charge	0 to 40°C
Discharge	-15 to +50°C
Storage	-15 to +50°C
Terminal type	Fast-on 4.8 mm
Material housing	ABS
Fire retardant	-
Weight	2.678 kg
Dimensions (W x H x D)	151 x 94 x 65 mm
VdS approval	available on some types

Ordering Information

Part No.	Description
BS127N	Sealed Lead-Acid Battery - 12V 7.2Ah - VdS approved
BS127NS3	Sealed Lead-Acid Battery - 12V 7.2Ah - V0 Flame Retardant Case



www.gesecurity.net

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-BS127N-2008-12-2 12:30:27 Released : 31.10.2007;