



GE
Security

Product Data Sheet

BS129N

Sealed Lead-Acid Battery - 12V 26Ah



Standard Features

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS129N

Sealed Lead-Acid Battery - 12V 26Ah

Specifications

Power supply	12 VDC
Nominal capacity	26 Ah, 20 h rate
Max. charge voltage at +20°C	13.8 VDC
Max. charge current	7.8 A
Max. discharge current	130 A
Internal approx. resistance	10 mohm
Temperature	
Charge	0 to 40°C
Discharge	-15 to +50°C
Storage	-15 to +40°C
Terminal type	MS bolt & nuts
Material housing	ABS
Fire retardant	-
Weight	9.528 kg
Dimensions (W x H x D)	166 x 175 x 125 mm
VdS approval	G101079

Ordering Information

Part No.	Description
BS129N	Sealed Lead-Acid Battery - 12V 26Ah - VdS approved
BS129NS3	Sealed Lead-Acid Battery - 12V 26Ah - V0 Flame Retardant Case



www.gesecurity.net

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-BS129N-2008-12-2 12:30:43 Released : 09.05.2007;