



GE
Security

Product Data Sheet

BS130N

Sealed Lead-Acid Battery - 12V 12Ah



Standard Features

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS130N

Sealed Lead-Acid Battery - 12V 12Ah

Specifications

Power supply	12 VDC
Nominal capacity	12 Ah, 20 h rate
Max. charge voltage at +20°C	13.8 VDC
Max. charge current	3.6 A
Max. discharge current	60 A
Internal approx. resistance	13 mohm
Temperature	
Charge	0 to 40°C
Discharge	-15 to +50°C
Storage	-15 to +40°C
Terminal type	Fast-on 6.35 mm
Material housing	ABS
Fire retardant	-
Weight	4.27 kg
Dimensions (W x H x D)	151 x 99 x 95 mm
VdS approval	G101080

Ordering Information

Part No.	Description
BS130N	Sealed Lead-Acid Battery - 12V 12Ah - VdS approved



www.gesecurity.net

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-BS130N-2008-12-2 12:30:58 Released : 09.05.2007;