



GE
Security

Product Data Sheet

BS132N

Sealed Lead-Acid Battery - 12V 45Ah



Standard Features

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS132N

Sealed Lead-Acid Battery - 12V 45Ah

Specifications

Power supply	12 VDC
Nominal capacity	45 Ah, 20 h rate
Max. charge voltage at +20°C	13.8 VDC
Max. charge current	13.5 A
Max. discharge current	225 A
Internal approx. resistance	5 mohm
Temperature	
Charge	0 to 40°C
Discharge	-15 to +50°C
Storage	-15 to +40°C
Terminal type	M5 bolt & nuts
Material housing	ABS
Fire retardant	-
Weight	14 kg
Dimensions (W x H x D)	198 x 166 x 171 mm
VdS approval	G102010

Ordering Information

Part No.	Description
BS132N	Sealed Lead-Acid Battery - 12V 45Ah - VdS approved



www.gesecurity.net

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-BS132N-2008-12-2 12:31:30 Released : 09.05.2007;