

PM831

Boxed Power Supply 24 VDC - 1 A



Kenmerken

- **Fault and mains present indicators**
- **Battery disconnect to prevent deep discharge**
- **Tamperswitch**
- **Fault output**
- **Mains and dc fuse**
- **Fully compliant with IEC65**
- **Transformers conform to BS145, VDE0550 & UL506**
- **Powder coated steel housing**

PM831

Boxed Power Supply 24 VDC - 1 A

Technische gegevens

Input voltage	230 VAC
	50 Hz \pm 10%
Output voltage	27.6 VDC
Load output	0.5 A
Total output	1 A
Output ripple	Max. 50 mVrms
Max. battery size	7.2 Ah (x2)
Battery recharge time	20
Battery disconnect voltage	19.6 \pm 0.2 VDC
Open collector output	Open circuit on fault or mains fail - 0 V - 100 mA
Fuse 12/24 V output	1.25 A
Fuse 230 VAC input	2 A
Operating temperature	-10 °C to +40 °C
Relative humidity	95%
Housing (steel) powder coated	1.2 mm
Dimensions (H x W x D)	275 x 330 x 80 mm

Bestelinformatie

Type nummer	Omschrijving
PM831	Boxed Power Supply 24 VDC - 1 A



GE Security

www.gesecurity.nl