Product Data Sheet



RXW8OM

Quik Bridge® 868 MHz Output Module

Expand with Wireless

Use the RF868 Quik Bridge® to add security protection to new areas of a building or extend a hardwire system; s range to secure the garage and other outside buildings that are too difficult to reach with hardwire devices.

Upgrade your customers to portable wireless keyfob devices, adding safety and convenience to their existing security system. Keyfobs are ideal for customers who do not want to memorise access codes, who want to turn on lights before entering premises or who do not like racing to beat entry or exit delays.

Wireless Zones

The RF868 Quik Bridge® combined with the RF868 wireless receiver allows eight wireless transmitters to be used on the wired inputs of any standard control panel.

Learn-ModeTM Technology

Patented Learn-ModeTM Technology increases the ease and reliability of installations. Each device in a system has its own factory-programmed identity so the receiver simply 'learns¿ the identity of each device. This dramatically reduces installation time and eliminates programming errors in the field.

Trouble Indication

The Quik Bridge® monitors the alarm, battery, tamper and supervisory status of transmitters learned into the eight zones. On-board LED¿s clearly indicate zone openings and closings and trouble conditions such as low battery and supervisory conditions.

Now every security system can be wireless. The RF 868 Quik Bridge® is compatible with standard hardwired control panels so your system can be easily expanded to incorporate a range of intrusion, fire and keyfob devices.



Standard Features

- 8 programmable zone outputs
- Supervised transmission
- Jamming detection
- Trouble & low battery output

RXW8OM

Quik Bridge® 868 MHz Output Module

Description

Specifications

| Current consumption | Output module: 60 mA |
|------------------------|------------------------------------|
| | Receiver: 30 mA |
| Operating temperature | -10 to +40°C |
| Dimensions (W x H x D) | 131 x 240 x 103 mm |
| Radio frequency | 868 MHz |
| Installation | Wall mount |
| Mains input | 12 VDC (supplied by control panel) |
| Colour | White |

Ordering Information

Part No. RX8W8CA-PCB

RF receiver 868 MHz 8-channel PCB only