

# Digi-LAN Network Camera IR-Dome

TV7218




## Specifications

CCD	1/3" Panasonic CCD	Resolution	380 TV lines
Light sensitivity	0.5 lux	Colour – B/W	Day/night (electronic switching from colour to B/W)
Lens	3.6 mm fixed lens / F2.0	Horizontal angle	78°
Network connection	10/100 BaseT–Ethernet (RJ45)	Protocols	TCP/IP, HTTP, FTP, SMTP, NTP, DHCP, DDNS
Supported browsers	Internet Explorer 5.x or higher	Compression method	MPEG4 or MJPEG
Resolutions	176 x 144, 352 x 288, 704 x 576	Frame rate	Max. 25 frames/second
Gain control	0 – 36 db (AGC)	Backlight compensation	BLC
White balance	Autom. white balance (AWB)	Electronic AES	1/50 – 1/100.000
Other connectors	1 x microphone & loudspeaker connection, 1 x alarm input (12 V DC, 50mA), 1 x alarm output (24 V DC 1A)	Other features	E–mail/FTP notification on alarm, pre– and post–alarm picture memory, opt. Bandwidth restriction
Ambient operating temperature	0 – 50°C	Ambient operating humidity	max. 90% non–condensing
Dimensions	Ø 137mm x 120mm (H)	Weight	ca. 1,070g
Scope of delivery	16–channel digital recorder software, power supply unit	Power supply	12 V DC, 1.5A
Protection type	Vandalism protected IP66	IR LEDs	24 IR LEDs (active below 2 Lux)
IR range	10 metres	Access protection	PIN code for Admin and users