

Digi-LAN Network Camera S/N-Dome – WLAN

TV7230

EcoLINE®

Produkthighlights:

- 1/4" Colour HQ-CMOS Sensor
- Max. Resolution 640 x 480 Pixel
- Realtime Video- and Audiostream Transmission
- Modern MPEG4 Codec
- Present-Position memorize function



Specifications

CCD	1/4" HQ CMOS sensor	Resolution	160 x 120, 320 x 240, 640 x 480
Light sensitivity	1.5 Lux / F2.0	Colour – B/W	Colour
Frame rate	Max. 25 frames/second	Lens	4 mm wide-angle lens
Network connection	1 x 1/100 BaseT-Ethernet (RJ45), 1 x W-LAN 802.11g	Network protocols	TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, DNS, DHCP, RTSP
Compression type	MPEG4	Supported browser	Internet Explorer 5.x or higher
Back-light compensation (BLC)	Backlight Compensation (BLC)	White balance	Autom. white balance (AWB)
Gain control	Autom. Gain Control (AGC)	Electronic AES	
Pan range	350°	Tilt range	90°
Microphone	integrated	Image overlay	Date and time
Bandwidth restriction	Optional	Access protection	PIN code for Admin and users
Alerting	E-mail, FTP	Status line	2-colour LED
Ambient operating temperature	0 –35°C	Ambient operating humidity	max. 90% / non-condensing
Weight	ca. 290g	Dimensions	100 (H) x 110 (D) mm
Power supply	12 V DC, 1.5A		