

# Digi-LAN Network Camera S/N-Dome – LAN

TV7240



## Produkthighlights:

- 1/4" Colour HQ-CMOS Picture Recording
- Max. Resolution 640 x 480 Pixel
- Realtime Transmission of Video- and Audiostreams
- Modern MPEG4 Compressionmode
- Present-Position recordable



| Specifications                |                                 |                               |   |
|-------------------------------|---------------------------------|-------------------------------|---|
| CCD                           | 1/4" HQ CMOS sensor             | Resolution                    | 160 x 120, 320 x 240, 640 x 480                                   |
| Light sensitivity             | 1.5 Lux / F2.0                  | Colour – B/W                  | Colour  |
| Frame rate                    | Max. 25 frames/second           | Lens                          | 4 mm wide-angle lens  |
| Network connection            | 1 x 1/100 BaseT-Ethernet (RJ45) | Network protocols             | TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, DNS, DHCP, RTSP |
| Compression type              | MPEG4                           | Supported browser             | Internet Explorer 5.x or higher                                   |
| Back-light compensation (BLC) | Backlight Compensation (BLC)    | White balance                 | Autom. white balance (AWB)  |
| Gain control                  | Autom. Gain Control (AGC)       | Electronic AES                |   |
| WLAN encryption:              | WEP 64/128 Bit, WPA-PSK         | Pan range                     | 350°  |
| Tilt range                    | 90°                             | Microphone                    | integrated  |
| Image overlay                 | Date and time                   | Bandwidth restriction         | Optional  |
| Access protection             | PIN code for Admin and users    | Alerting                      | E-mail, FTP   |
| Status line                   | 2-colour LED                    | Ambient operating temperature | 0 –35°C   |
| Ambient operating humidity    | max. 90% / non-condensing       | Weight                        | ca. 290g  |
| Dimensions                    | 100 (H) x 110 (D) mm            | Power supply                  | 12 V DC, 1.5A   |