

wireless siren are outweighed by complicated installation and wiring costs. The MCS-730 two-way, fully wireless outdoor siren overcomes these challenges through easy, cabling-free installation and optional extended time between battery changes, for long-lasting operability. In addition, two-way and fully supervised communication with the control panel assures highly reliable operation.

This affordable siren's sleek design ensures it is clearly visible, alerting and deterring potential intruders, while maintaining the clean look of any building. In the event of an alarm, the siren sounds loudly and the strobe light is activated, ensuring the alarm is noticed.

- Sleek design and high power strobe light provide visual deterrence to potential intruders, while maintaining a clean building facade
- Large free screen-print area
- Choice of red, blue, amber or transparent strobe light lens
- Easy, cabling-free installation
- Robust design and weatherproof housing
- Two diversity antennas for optimal wireless performance



MCS-730

Key Features & Benefits

Versatile solution fits varied design needs

- Contemporary, sleek design with choice of red, blue, amber or transparent strobe light lens
- Large free screen-print area available for company logo and information

Highly reliable and cost-effective

- Two-way fully-supervised communication with the control panel
- Comfort light (LED) flashes every few seconds to indicate that the siren is active and deter intruders.
- Two diversity antennas for optimal wireless performance
- Audible and visual notifications of intrusions, fires, low battery voltage, and communication disruptions
- Issues a different alarm sound for burglaries and fires
- · Audial arming and disarming confirmation
- 110dB piezo siren
- High-power strobe light
- Double tamper protection (wall and cover)
- IP55 rating, with increased protection from dust and moisture
- Robust design for protection against harsh external conditions including UV radiation from direct sunlight

Easy to install and maintain

- Fully wireless, battery-operated, with no power supply required
- Convenient and rapid no-mess installation
- Option of two batteries to enable longer life*
- Self-test for checking the siren and strobe lights prior to installation

Compatible with selected versions of PowerMax™Pro, PowerMaxComplete and PowerMaxExpress***



Specifications

Power supply: 3.6v non rechargeable Lithium battery

Battery life expectancy: 3 years (with typical use)*

Sound output: 110dB@1m

Operating frequency (MHz): 315, 433.92, 868.95

Strobe frequency rate: 1 flash per second

Dimensions (L x W x D): 295 x 186 x 63mm

(11-5/8 x 7-5/16 x 2-1/2in)

Weight (including battery): 970g (34oz)

Operating temperature: -25° - 70°C (13° - 158°F)

Certifications: EN 50131-1 Grade 2 Class 4,

CFR Part 15, RSS210, IP55,

EN 30131-4

■ **Visonic**, and PowerMax are registered trademarks of Visonic Ltd. Other names are the property of their owners. Visonic reserves the right to change information or specifications without notice.

VISONIC LTD. MCS-730 DATA SHEET ENGLISH C-800498 (Rev.01)

Designed by: Linor Ankri

^{*} Only one battery included. The second battery to extend life must be purchased separately.

^{**} Check the control panel's manual for compatibility.