

DC138

Industrial flush mount contact for steel door, high security grade 3, white

Requirements for grade 3 magnetic contacts

The grade 3 magnetic contacts are high security contacts which do meet the following requirements: preciseness of opening distance, magnet polarisation, strength of the magnet

Model with built in EOL resistors available

Though built in EOL resistors are not mandatory according to EN50131-2.6 requirements, Interlogix offers a model with built in EOL resistors for a quick installation (see how to Order information)



Standard Features

- EN 50131-2-6 Grade 3 and VDS certified
- 2m cable
- Tamper protected
- Several European certifications

DC138

Industrial flush mount contact for steel door, high security grade 3, white

Specifications

General	
Application type	Recessed Mount
Contact type	1 pin NC contact
Connectivity	LIYY 4 x 0.14 mm Cu tin-plated; Suitable for LSA IDC method of termination
Wired/wireless	
Wired-wireless	Wired
Electrical	
Voltage	max 100V DC
Contact power	max 6W or 6 VA
Switching current	max 500mA
Contact resistance	max 0.15 Ohm
Physical	
Colour	White
Material	ABS
Dimensions magnet	6 x 19 mm
Dimensions contact / sensor	8 x 32 mm
Operating gap	12 mm
Environmental	
Operating temperature	-25 to 70°C
IP rating	IP67
Standards & regulation	
EN50131 grade	Grade 3

Ordering Information

Part No.	Description
DC138	Industrial flush mount contact for steel door, high security grade 3, white
DC138S60	Industrial flush mount contact for steel door, high security grade 3, white, 6m cable
DC138R4.7	Industrial flush mount contact for steel door, high security grade 3, white with 4k7 EOL resistor