



# TVB-1102

3 MPX Full HD Outdoor IR Bullet Camera, Fixed 6mm, PAL

## Overview

The TVB-1102 is a Full HD IP Outdoor IR Bullet camera, designed to perform in a wide range of lighting conditions. Its built-in IR LEDs provide illumination up to 25 meters to ensure images – even in low light environments. The camera's Digital Wide Dynamic Range feature ensures that images are obtained, even in backlight scenes. The camera is compliant with the ONVIF and PSIA open standards.

## Form Factor

The size of this mini bullet camera makes it easy to install, for example, at entry or exit doors. The IP66 rated housing provides a weatherproof solution.

## IP technology

TruVision cameras utilize H.264 compression with dual-streaming capability, making it easy to manage the camera's bandwidth usage.

These cameras have been designed to adhere to PSIA and ONVIF open communication standards, and also support a CGI command set for simple integration into any IP system. Video streams can be set up for high and low bandwidth and images can be streamed for live viewing or sent to a designated recording location.



- IR bullet camera
- Real time Full HD 1080p resolution
- Maximum resolution QXGA (2048 x 1536)
- H.264 with dual streaming functionality
- 1/3" CMOS Progressive Scan
- Motorized IR cut filter
- Digital Wide Dynamic Range
- 0 Lux (IR on)
- Up to 25m IR illumination
- Fixed 6mm lens
- Designed to ONVIF and PSIA open standards

# TVB-1102

## 3 MPX Full HD Outdoor IR Bullet Camera, Fixed 6mm, PAL

Camera		
Sensor Size:	1/3'	
SD / MPX:	3MPX	
Sensor scan:	Progressive Scan	
Sensor type:	CMOS	
IP Compression / Standard:	Main stream: H.264 H.264/MJPEG	Sub stream:
Available Resolutions:	Main stream: 2048x1536, 1920x1080, 1280x720 Sub stream: 704x576, 352x288, 320x240	
Maximum Resolution (@ FPS):	2048 x 1536 @ 12.5 fps	
Maximum Real Time Resolution:	1920 x 1080	
HD 720p:	Yes	
Full HD 1080p:	Yes	
Digital S/N ratio:	50dB	
Electronic shutter:	1/25s to 1/100.000s	
Certification:	UL, CE, FCC, C-tick, REACH, RoHS, HALT, WEEE	
Lighting performance		
Wide Dynamic Range:	DWDR	
WDR in dB:	72dB	
Digital noise reduction:	3D DNR	
Day/Night:	True Day/Night	
Motorized IR Cut Filter:	Yes	
Color sensitivity:	0.01 lux @ F1.2	
B/W sensitivity:	0 Lux with IR	
IR sensitivity:	0 Lux with IR	
IR Range:	Up to 25m	
IR Wavelength:	850nm	
B/W trigger:	2.61lux	
IR trigger:	2.61lux	
Housing		
Camera type:	Bullet	
IP rating:	IP 66	
Outdoor:	Yes	
Rugged:	No	
Lens		
Control type:	Fixed	
Optical zoom:	No	
Focal length:	6mm	
F-stop:	2	
Autoiris:	No	
Varifocal:	No	
Zoom lens:	No	
Autofocus:	No	
Power consumption		
Voltage Input:	12VDC $\pm$ 10%	
Current:	Max. 0.42A	
Power Consumption:	Max. 5W	
PoE:	PoE(802.3af)	
Network		
ONVIF:	2.2	
PSIA:	1.1	
CGI:	Yes	
Network Protocols:	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP, 802.1x, Qos, IPv4/IPv6	
Local Storage		
Media:	No	
Capacity:	No	
Camera Analytics		
Motion Detection:	Yes	
Privacy Masking:	4	
Mechanical / Environmental		
Dimensions:	$\varnothing$ 60 x 153mm (2,4 x 6 in)	
Weight:	373g (0.82lb)	
Cold start Temperature:	-20°C (-14°F)	
Operating Temperature:	-30°C to 60°C (-22°F to 140°F)	

