



# TVT-6101

## TruVision HD-TVI Analog Turret Camera, 5MPX, 2.8MM Lens, True D/N, WDR, 30m IR HD-TVI Output, Coax OSD Control, , IP67

### Overview

---

The TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations. Designed for optimal image quality over existing coaxial cable, options are available at up to 8Mpx resolution.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome, traditional bullet and turret cameras . Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP67 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



### Details

---

- 5MPx HD-TVI resolution
- HD-TVI technology for transmitting high quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 30 m
- IP67 environmental rating
- True wide dynamic range
- 2.8 mm lens
- 12 VDC
- Adapter plate included
- Provide OSD functionality via TruVision up the coax control

# TVT-6101

TruVision HD-TVI Analog Turret Camera, 5MPX, 2.8MM Lens, True D/N, WDR, 30m IR HD-TVI Output, Coax OSD Control, , IP67

## Technische specificaties

### General

Technology	HD-TVI analog
Video standard	NTSC, PAL
Image settings	Mirror
Video output	BNC Composite PAL / NTSC, HD-TVI

### Camera

Max. resolution	5 MP
Sensor scan	Progressive
Sensor type	CMOS
Effective pixels (H x V)	2560 x 1944
Shutter time	1/25s (PAL) or 1/30s (NTSC) to 1/50,000

### Lighting performance

WDR type	True WDR
WDR	130 dB
Day/night	True Day/Night
Motorized IR cut filter	Yes
Color sensitivity	0.003 Lux @ (F1.2, AGC ON)
B/W sensitivity	0 Lux with IR
Infrared (IR)	Yes
IR range	30m

### Lens

Lens type	Fixed
Focal length	2.8 mm
f-stop	f1.2
Auto iris	Yes

### Electrical

Operating voltage	12VDC
Power supply type	12 VDC
Power consumption	5.8 W Max.

### Physical

Physical dimensions	Ø 110 x 91 mm
Net weight	310 g
Colour	Grey (Pantone 428c)
Material	Aluminium
Form Factor	Turret

### Environmental

Environment	Indoor / Outdoor
Operating temperature	-40 to 60°C
Relative humidity	90% or less (non-condensing)
IP rating	IP67

### Regulatory

Compliance	CE, REACH, RoHS, WEEE
------------	-----------------------

### Compatible TruVision Recorders/Encoders

TVR12HD	(View Max 1080p, Record Max. 1080p @ 12 fps)
TVR44HD	(Record/View Max. 1080p)
TVR15HD	(Record/View Max. 5Mpx @ 12fps)
TVR45HD	(Record/View Max. 5Mpx @ 12fps)
TVR46HD	
TVE-110/410/810/1610	
TVE-120/420/820/1620	

### Supported Accessories

TVD-BB3	Back box
TVD-BB3A	Back box
TVD-CB3 (with adapter plate)	Cup base
TVD-M2-WM (with adapter plate)	Wall mount

Als een bedrijf van innovatie behoudt Carrier Fire & Security zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar [nl.firesecurityproducts.com](http://nl.firesecurityproducts.com) of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 1 July 2021 - 10:37

